

Diesel Tank 12 Volt, 220 lt with lid and flow-meter



Codice: **428/220-KC**




Complete kit on tank 220 LT. To transfer diesel. IN TOTAL EXCLUSION ADR 1.1.3.1. c. With flow-meter, 4 mt rubber hose and aluminum gun with automatic stop. With a self-priming, self-priming piston electric motor, equipped with a bypass valve and filter, brush motor powered by low-voltage DC current with intermittent loop, closed in IP55 protection class, directly flanged to the pump body. Battery cables: length 2 mt. Connections: Thread Ø 1 ". All the components are appropriately mounted on a polyethylene tank, with a filling cap with safety valve, inlets for lifting when full with forks and handles for lifting when empty. Use only with diesel: Viscosity 2 to 5.35 Cst (at 37.8 ° C) and minimum flash point (PM) of 55 ° C

Allowed fluids	DIESEL
Capacity	220 LT
DIM Height	750 MM
DIM Length	800 MM
DIM Width	600 MM
Duty cycle	30 min

Entry diameter	1"
Exit diameter	1"
Flow-rate	40 LT/MIN
Material	PLASTIC, STEEL - BODY IN CAST IRON, VANES IN PLASTIC RESIN, ROTOR IN STEEL
Maximum suction height	2-3 mt
Multiple packing	PALLET 6 PCS
Not allowed fluids	GASOLINE, INFLAMMABLE LIQUIDS WITH PM<55°C, LIQUIDS WITH VISCOSITY >20 Cst, WATER, FOOD LIQUIDS, CORROSIVE CHEMICAL FLUIDS AND SOLVENTS
Operating temperature	-20 ÷ 60 °C
Origin	MADE IN ITALY
Real capacity	195-200 LT
Regulations	2006/42/CE & 2006/95/CE & 2004/108/CE
Single packing	NOT AVAILABLE
Thread	1"
Vertical lift	12 mt
Voltage	12 V
Working	ELECTRIC

Accessori già inclusi



Pistola per travaso con arresto automatico

Codice articolo: **227**



Diesel Pump 12 Volt

Codice articolo: **228/F**

**CONTALITRI DIGITALE PER GASOLIO E BENZINA**Codice articolo: **543/C****Tappo per serbatoio**Codice articolo: **580/2G****Tubo di uscita in gomma**Codice articolo: **745/U**

Accessori disponibili

**Filtro a cartuccia**Codice articolo: **578/O-30****Tappo per serbatoio**Codice articolo: **580/2G****Cinghia di fissaggio**Codice articolo: **588**